

[Jan-2019] Download Braindump2go 300-365 Dumps for Free (Q85-Q95)

2019/Jan Braindump2go 300-365 Exam Dumps with PDF and VCE New Updated Today! Following are some new 300-365 Real Exam Questions:]

1. [2019 Latest 300-365 Exam Dumps (VCE & PDF) Instant Download:

<https://www.braindump2go.com/300-365.html>2. [2019 Latest 300-365 Exam Questions & Answers Download:
<https://drive.google.com/drive/folders/0B75b5xYLjSSNZTJ3Y0Z5b0NFRFE?usp=sharing> QUESTION 85A sporting arena has a new wireless network and finds that clients are not connecting to their nearest access point. Which setting can be enabled to minimize this behavior and reduce the AP view of channel utilization?
A. Use an RF profile with an RX-SOP threshold.
B. Enable Band Select
C. Enable Client Balancing
D. Turn on CleanAir
Answer: A QUESTION 86 Which option is a calibration of a Cisco MSE deployment limited to when that deployment is using the linear point collection method?
A. rogue AP
B. associated 802.11 a/n clients
C. RFID tag
D. associated 802.11 b/g/n clients
Answer: A Explanation:

https://www.cisco.com/c/en/us/td/docs/wireless/mse/8-0/MSE_CMx/8_0_MSE_CAS/7_4_MSE_CAS_chapter_01010.html

QUESTION 87 When CAPWAP protocol runs over IPv4, which UDP port numbers are used for control and data traffic, respectively?
A. control 5246, data ?UDP-Lite(IP Protocol 136)
B. control 5247, data ?5246
C. control 5246, data ?5247
D. control 5247, data ?UDP-Lite(IP Protocol 136)
Answer: C QUESTION 88 An engineer has deployed a WLAN in a high-density auditorium and expects the number of clients to grow. Which WLC configuration can be used to increase the IP space without any service disruptions?
A. dynamic interface
B. interface group
C. AP group
D. RF group
Answer: B QUESTION 89 A security engineer wants all guest users to be terminated on the DMZ of their firewall. Which two configurations must be implemented to fulfill this new requirement? (Choose two.)
A. TCP port 16666 and 16113 in an ACL on the controller
B. UDP ports 16666 and IP protocol 97 on the firewall
C. a mobility group with a controller in an isolated network on the firewall
D. an RF group with a controller in an isolated network on the firewall
E. UDP ports 1812 and 1645 in an ACL on the controller
Answer: B QUESTION 90 Which two access categories could use TXOP value higher than 0, as per 802.11e standard? (Choose two.)
A. AC_VO
B. AC_BK
C. AC_VI
D. AC_BE
E. AC_NL
Answer: A Explanation:

<https://www.cisco.com/en/US/docs/solutions/Enterprise/Mobility/emob30dg/WANQoS.pdf> QUESTION 91 A wireless engineer is configuring a Cisco MSE by using the automatic installation script. Which two parameters are mandatory and must be configured at least once? (Choose two.)
A. Ethernet interface
B. hostname
C. GRUB password
D. domain name
E. NTP server
Answer: A Explanation: Please note that the following parameters (indicated by *) are mandatory and must be configured at least once.
-> Hostname
-> Network interface eth0
-> Timezone
-> Root password
-> NCS Communication username
-> NCS Communication password
https://www.cisco.com/c/en/us/td/docs/wireless/mse/7-6/Virtual_appliance/Installation_Config_Guide/Cisco_MSE_VA_Config_Guide/Installing_MSE_Virtual_Appliance.html QUESTION 92 Clients on access points within an AP group are not receiving multicast traffic after roaming to another AP within the AP group. Which configuration must be done to maintain multicast connectivity?
A. Enable an ACL on the router that serves the VLAN or subnet.
B. Enable NAC out-of-band support.
C. Enable a unique NAS-ID for the AP group.
D. Enable IGMP snooping.
Answer: D Explanation:

<https://www.cisco.com/c/en/us/support/docs/wireless-mobility/wireless-lan-wlan/81671-multicastwlc-lap.html>

QUESTION 93 Which two parameters are used by MSE location analytics to determine the behavior of a Wi-Fi device? (Choose two.)
A. the transmit power
B. the Wi-Fi channel
C. the dwell time
D. the path choice
E. Layer 2 roaming
Answer: C Explanation: **https://www.cisco.com/c/en/us/td/docs/wireless/mse/3350/7-4/Location_Analytics_Service/Guide/Cisco_Location_Analytics_Service_Configuration_Guide/Location_analytics_overview.html** QUESTION 94 A customer is concerned that the mesh network will not converge quickly enough because of the 20 percent premium that is given to the selected parent. What is the purpose of the premium?
A. It speeds up convergence.
B. It uses SNR, regardless of the premium.
C. It prevents link flapping.
D. It creates a list of other potential parents.
Answer: B Explanation:

https://www.cisco.com/c/en/us/td/docs/wireless/technology/mesh/8-3/b_mesh_83/Site_Preparation_and_Planning.html

QUESTION 95 An engineer needs to address roaming issues with sticky clients in high-density areas on a campus. Which feature must the engineer configure?
A. Layer 3 roaming
B. load balancing and band select
C. optimized roaming
D. Layer 2 roaming
Answer: D!!!RECOMMEND!!!1. [2019 Latest 300-365 Exam Dumps (VCE & PDF) Instant Download:

<https://www.braindump2go.com/300-365.html>2. [2019 Latest 300-365 Study Guide Video: YouTube Video:

[YouTube.com/watch?v=IAyeIIszH4I](https://www.youtube.com/watch?v=IAyeIIszH4I)